2027 CAN-AM MAVERICK X3 X RC TURBO RR



Loft Green Satin

PACKAGE HIGHLIGHTS

- Smart-Lok™* front differential
- FOX† 2.5 and 3.0 PODIUM RC2† shocks with bypass
- Belt monitoring system
- 850-W magneto
- 32 in. XPS Hammer King Tyres
- 15 in. aluminum beadlock wheels
- 4-point harness with shoulder pads
- Front bumper, half-doors, full hard roof, intrusion bar
- 4,500 lb (2,041 kg) winch with synthetic cable
- New window nets
- 2 person seating capacity
- HMWPE differential and under bumper skid plates
- HMWPE front and rear suspension arm
- UHMWPE rock sliders
- Rear tow hook
- 10.25 in. Touch display with telescopic steering wheel and front & rear camera
- X-package graphics/seats
- Can-Am LED signature lights

ENGINE	TURBO RR
Type	200 hp, Rotax® ACE (Advanced Combustion Efficiency) 900 cc Turbocharged triple-cylinder engine, liquid cooled with integrated intercooler and high-performance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	pDrive primary and Quick Response System X (QRS-X) CVT with high airflow, L / H / N / R / P
Drive Train	Lockable front differential with exclusive Smart-Lok™* technology. True 4-mode traction system: 2WD / 4WD with front diff. lock / 4WD ROCK / 4WD TRAIL
Power Steering	High torque Tri-Mode Dynamic Power Steering (DPS™)

SUSPENSIONS	
Front Suspension	Arched double A-arm with sway bar / 22 in. (55.9 cm) suspension travel Trophy truck inspired arms
Front Shocks	FOX† 2.5 PODIUM RC2† Piggyback with bypass, dual-speed compression and rebound adjustments
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar and arched lower links / 24 in. (61 cm) suspension travel
Rear Shocks	FOX† 3.0 PODIUM RC2† with bypass, dual-speed compression and rebound adjustments

TYRES & WHEELS	
Front / Rear Tyres	XPS Hammer King 32 x 10 x 15 in.
Wheels	15 in. cast-aluminum beadlock

BRAKES	
Front	Twin piston caliper (32 mm) / 262 mm discs
Rear	Twin piston caliper (28 mm) / 248 mm discs

DIMENSIONS & CAPACITIES	
Estimated Dry Weight	1,845 lb (837 kg)
Cage	Dual-phase 980 steel
L x W x H	134.5 x 72.8 x 68.5 in. (341.6 x 184.9 x 174 cm)
Wheelbase	102 in. (259.1 cm)
Ground Clearance	16 in. (40.6 cm)
Rack Capacity	200 lb (91 kg) with LinQ™ quick-attach
Storage Capacity	Total: 2.5 gal (9.4 L)
Fuel Capacity	10.5 gal (40 L)
Person Capacity	2

FEATURES	
Gauge	4.5 in. Digital display with keypad & 10.25 in. Touch display
Battery	18 Ah (270 CCA)
Magneto	850 watts
Instrumentation	DC outlet (10-A)
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Lighting	Premium high-performance LED headlights LED taillights LED signature lights
Winch	4,500 lb (2,041 kg) winch with synthetic cable
Protection	Front bumper • Full hard roof • Premium half doors • Window net • Intrusion bar • 4-point harness with shoulder pads • UHMWPE rock sliders • HMWPE skid plates: Full heavy duty with differential / under bumper / front and rear suspension arm • Rear tow hook • Trailing Arm protector • Lower A-arm protector

WARRANTY	
Factory Warranty	3-year unlimited km powertrain & Rotax® engine warranty

can-am

CAN-AM ATV/SSV 3 YEAR UNLIMITED KM WARRANTY POWERTRAIN & ROTAX® ENGINE

©2026 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. †Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Some models depicted may include optional equipment. Read the side-by-side vehicle (SxS) operator's guide and watch the safety DVD before driving. For your safety, wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding, alcohol and drugs don't mix. SxSs are for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 16 years old. Passenger must be at least 12 years old and able to hold hand grips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed. Ride responsibly. +Manufacturer's limited warranty. Does not affect consumer guarantees. Available on MY23 Outlander Pro, MY24/MY25/MY26/MY27 ATV and MY24/MY25/MY26/MY27 SSV models.

BRP